

INCOMPATIBILITY (MATERIAL TO AVOID):

Alkaline materials, strong acids and oxidizing materials.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources; provide good ventilation; dike spill area and add absorbent material to spilled liquid. Thoroughly wet with water and mix.

WASTE DISPOSAL METHOD:

Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state and federal hazardous waste regulations before disposing into approved hazardous waste landfills. Obey relevant laws.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

When spraying and/or printing this material, use a niosh-approved cartridge respirator or gas mask suitable for airborne mists and vapor concentrations below the time-weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.

VENTILATION:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentration below TLV. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES: Impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use chemical safety glasses, goggles and face shields for eye protection.

PROTECTIVE EQUIPMENT:

Use impermeable aprons and protective clothing when ever possible to prevent skin contact. The use of head caps when ever possible is strongly recommended.

HYGIENIC PRACTICE: Eye washes and safety showers in the work place is recommended.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use non-sparking utensils when handling this material. Avoid hot metal surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.

OTHER PRECAUTIONS:

Smoking in areas where this material is used should be strictly prohibited. Tools used with this material should be aluminum, brass or copper. Plastic tools should not be used. Since emptied containers retain product residues, (vapors, liquid and/or solid) all hazard precautions should be observed.

SECTION X - TRANSPORTATION DATA

PROPER SHIPPING NAME: PAINT UN1263 WATER REDUCIBLE

DOT CLASSIFICATION: COMBUSTIBLE DOT LABEL: RED

PRECAUTIONS TO BE TAKEN IN TRANSPORTATION: Refer to Section IX KEEP FROM FREEZING

N : THIS INFORMATION IS ACCURATE TO THE BEST KNOWLEDGE OF ADVANCED COATINGS & CHEMICALS COMPANY, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.